



ACRYLQUARZ

acrylic paint for exteriors, available in multiple grain sizes

Description	Water-based paint composed of: acrylic resins in emulsion, aggregates, pigments, additives, bactericides, water repellents		
	specific weight		1,53-1,57
	pH		8-9
	thinner		water
Characteristics	washability		high
	vapor permeability		good
	volatile organic components		VOC < 30 gr/lt
	environmental classification		A
Safety	no requirement for specific labelling		
Storage	1 year in the original packaging if stored between +5°C and +40°C		
Supports	It is applied, externally and internally, on cement mortars, concrete, prefabricated panels, plasters, old water-based paints and plasters that are well preserved and adherent to the support. These grounds must be absorbent, flat, clean, healthy and dry. Prefabricated buildings must not contain traces of disarming agents. Old or crumbling surfaces must be cleaned and consolidated. Do not apply on surfaces subject to rising damp.		
Laying Rules	Laying and drying must be carried out between + 5°C and + 35°C, away from bad weather or excessive sun		
Laying	Dilute with clean water and apply in two coats with a brush, roller or gun.		
	dilution	first coat	20%
		second coat	5-10%
	Interval between two passes		10-12 hours
	Overpainting		24 hours
	Cleaning of tools		water
Types and yields	fine grain		7.5-8.5 m ² /lt/pass
	medium grain		6.5-7.5 m ² /lt/pass
	grain no. 5		5-6 m ² /lt/pass

This edition cancels and replaces any previous edition. It is the task of Messrs. Customers ensure that this document has not been canceled by a subsequent edition. Edition 2023