



VELARIS

siloxane glaze for exterior and interior

Description	Transparent glaze, ready to use, composed of: siloxane resins in aqueous emulsion, dyes, additives, bactericides specific gravity pH thinner	1.02-1.06 8-9 water
Characteristics	steam transmission μ water absorption according to DIN 52617 environmental classification Velaris can be applied outdoors and indoors as a matt glaze over an underpainting. If applied over a good quality, slightly absorbent paint, Velaris has a very long open time, and involves practically no risk of visible recurrence.	< 12 0.3-0.4 kg/m ² /24h A
Safety	no requirement for specific labelling	
Storage	1 year in the original packaging if stored between +5°C and +40°C	
Suppots	Velaris is applied, inside or outside, over paints that are washable and not very absorbent. For basic paints, the general installation rules apply: the supports must be flat, clean, healthy and dry, prefabricated structures must not contain traces of release agents, old or crumbling surfaces must be clean and consolidated. Plaster and wood must be treated with a suitable fixative	
Laying Rules	Laying and drying must be carried out between +5°C and +35°C, protected from bad weather or excessive sun. Do not apply materials from different batches on the same wall	
Laying	Spread Velaris with a sponge or brush, in an irregular manner. It is advisable to provide at least two passes, so that with the next one you can, if necessary, 'touch up' the effect of the previous one. In this regard, however, consider that each pass increases the chromatic intensity and coverage of the glaze. The dilution can vary from 10-15% to over 50%, depending on whether you want a highly contrasted or rather soft look. Wash tools with water after use.	
Yeld	over washable paint	10-12 m ² /lt

This edition cancels and replaces any previous edition. It is the task of Messrs. Customers ensure that this document has not been canceled by a subsequent edition. Edition 2023