



DURIBETON

exterior acrylic paint suitable for protecting concrete elements

| | | | |
|-----------------|---|-------------|-----------------|
| Description | Water-based paint composed of: acrylic resins in emulsion, aggregates, pigments, additives, bactericides, water repellents | | |
| | specific weight | | 1,34-1,38 |
| | pH | | 8-9 |
| | thinner | | water |
| Characteristics | washability | | very high |
| | vapor permeability | | low |
| | volatile organic components | | VOC < 30 gr/lit |
| | environmental classification | | A |
| Safety | no requirement for specific labelling | | |
| Storage | 1 year in the original packaging if stored between +5°C and +40°C | | |
| Supports | It is applied externally and internally on concrete, prefabricated concrete panels, cement plasters. These grounds must be absorbent, flat, clean, healthy and dry. Prefabricated buildings must not contain traces of disarming agents. Old or crumbling surfaces must be cleaned and consolidated. Do not apply on surfaces subject to rising damp. | | |
| Laying Rules | Laying and drying must be carried out between + 5°C and + 35°C, away from bad weather or excessive sun | | |
| Laying | Dilute with clean water and apply in two coats with a brush, roller or gun. | | |
| | dilution | first coat | 10-15% |
| | | second coat | 5-10% |
| | Interval between two passes | | 10-12 hours |
| | Overpainting | | 24 hours |
| | Cleaning of tools | | water |
| Yield | 7-8 m ² /lt/pass | | |

This edition cancels and replaces any previous edition. It is the task of Messrs. Customers ensure that this document has not been canceled by a subsequent edition. Edition 2023