



## VELO ANTICO

*acrylic glaze for exterior and interior*

Description	Transparent glaze, ready to use, composed of: acrylic resins in aqueous emulsion, dyes, additives, bactericides specific gravity pH thinner	1.02-1.06 8-9 water
Characteristics	water absorption washability environmental classification	very low washable A
Safety	no requirement for specific labelling	
Storage	1 year in the original packaging if stored between +5°C and +40°C	
Suppots	<p>Velo Antico is applied, inside or outside, over paints that are washable and not very absorbent. It is necessary that the absorption of the base is low, because Velo Antico has a relatively short open time, which would be further reduced by a high absorption base.</p> <p>For basic paints, the general installation rules apply: the supports must be flat, clean, healthy and dry, prefabricated structures must not contain traces of release agents, old or crumbling surfaces must be clean and consolidated. Plaster and wood must be treated with a suitable fixative</p>	
Laying Rules	Laying and drying must be carried out between +5°C and +35°C, protected from bad weather or excessive sun. Do not apply materials from different batches on the same wall	
Laying	<p>Spread Velo Antico with a sponge or brush, in an irregular manner. It is advisable to provide at least two passes, so that with the next one you can, if necessary, 'touch up' the effect of the previous one.</p> <p>In this regard, however, consider that each pass increases the chromatic intensity and coverage of the glaze.</p> <p>The dilution can vary from 10-15% to over 50%, depending on whether you want a highly contrasted or rather soft look.</p> <p>Wash tools with water after use</p>	
Yeld	over washable paint	10-12 m2/lit

*This edition cancels and replaces any previous edition. It is the task of Messrs. Customers ensure that this document has not been canceled by a subsequent edition. Edition 2023*